

CABLE REEL



STANDARD STARTER UNITS

Part No.	Width	Depth	Height	Weight
CR-24-24-96	24"	24"	96"	112.38
CR-36-24-96	36"	24"	96"	120.03
CR-48-24-96	48"	24"	96"	127.65
CR-24-36-96	24"	36"	96"	116.77
CR-36-36-96	36"	36"	96"	124.42
CR-48-36-96	48"	36"	96"	132.04

CR-24-24-120	24"	24"	120"	142.68
CR-36-24-120	36"	24"	120"	152.88
CR-48-24-120	48"	24"	120"	163.04
CR-24-36-120	24"	36"	120"	145.46
CR-36-36-120	36"	36"	120"	155.66
CR-48-36-120	48"	36"	120"	165.82

CR-24-24-144	24"	24"	144"	160.58
CR-36-24-144	36"	24"	144"	170.78
CR-48-24-144	48"	24"	144"	180.94
CR-24-36-144	24"	36"	144"	165.58
CR-36-36-144	36"	36"	144"	175.78
CR-48-36-144	48"	36"	144"	185.94

Green Uprights and Orange Beams

Standard Starter Units

8' units include:

2 uprights, 3 tie beams, 3 sets of axle brackets

10' & 12' units include:

2 uprights, 4 tie beams, 4 sets of axle brackets

STANDARD ADDER UNITS

Part No.	Width	Depth	Height	Weight
CR-24-24-96A	24"	24"	96"	71.28
CR-36-24-96A	36"	24"	96"	78.93
CR-48-24-96A	48"	24"	96"	86.55
CR-24-36-96A	24"	36"	96"	73.47
CR-36-36-96A	36"	36"	96"	81.12
CR-48-36-96A	48"	36"	96"	88.74

CR-24-24-120A	24"	24"	120"	91.46
CR-36-24-120A	36"	24"	120"	101.66
CR-48-24-120A	48"	24"	120"	111.82
CR-24-36-120A	24"	36"	120"	92.85
CR-36-36-120A	36"	36"	120"	103.05
CR-48-36-120A	48"	36"	120"	113.21

CR-24-24-144A	24"	24"	144"	100.41
CR-36-24-144A	36"	24"	144"	110.61
CR-48-24-144A	48"	24"	144"	120.77
CR-24-36-144A	24"	36"	144"	102.91
CR-36-36-144A	36"	36"	144"	113.11
CR-48-36-144A	48"	36"	144"	123.27

Standard Adder Units

8' units include:

1 upright, 3 tie beams, 3 sets of axle brackets

10' & 12' units include:

1 upright, 4 tie beams, 4 sets of axle brackets

AXLE BRACKETS

Part No.	Capacity	Weight
I4500	2000#/Pair	3#/Pair

Width dimensions between columns - net axle brackets. Cut size for axle is 1/2" less than actual width. Example 24" wide unit - use 23-1/2" axles. Max. rod diameter 1 5/8".

BODE

MATERIAL HANDLING SOLUTIONS

BodeEquipment.com
(800)797-5699